

**Physics Formula Revision (Conditions highlighted in red) [Draft Ver]**

Topic	Formula	SI unit	Final unit
2.1: Kinematics	Speed = $\frac{\text{Distance}}{\text{Time}}$	Distance (m) Time (sec)	m/s
	Velocity = $\frac{\text{Displacement}}{\text{Time}}$ ; $v = \frac{s}{t}$	Displacement (m) Time (sec)	m/s
	Acceleration = $\frac{\text{Diff. in Velocity}}{\text{Time}}$ <b>Condition: Used only when acceleration is constant.</b>	Velocity (m/s) Time (sec)	m/s <sup>2</sup>
2.2 Dynamics	Resultant Force = Mass × Acceleration $F = ma$	Force (N) Mass (kg) Acceleration (m/s <sup>2</sup> )	Newton (N)
2.3 Mass Weight Density	$W = mg$	Mass (kg) g = 10 N/kg	Newton (N)
	...(Density) = $\frac{m}{V}$ ;:	Mass (g/kg) Volume (cm <sup>3</sup> /m <sup>3</sup> )	g/cm <sup>3</sup> or kg/m <sup>3</sup>
2.4 Turning Effect of Forces	Moments = $Fd$	Force (N) Perpendicular Distance (m)	Newton metre (Nm)
	Note: <b>Perpendicular Distance is not always the length of the rod.</b>		
2.5 Pressure	Solids: Pressure = $\frac{\text{Force}}{\text{Area}} = \frac{F}{A}$	Force (N) Area (m <sup>2</sup> )	N/m <sup>2</sup> , Pa
	Liquids: Pressure = $h \dots g$	h (m): Depth of Liquid ... (kg/m <sup>3</sup> ): Density of liquid g: 10N/kg	N/m <sup>2</sup> , Pa
	Gases ( <b>when temp. is constant</b> ) $P_1V_1 = P_2V_2$	P (Pa): Pressure V (m <sup>3</sup> ): Volume	NA
2.6 Energy, Work, power	$W(\text{Work Done}) = Fd$	F (N): Force d (Perpendicular dist): m	J
	$K.E.(\text{Kinetic Energy}) = \frac{1}{2}mv^2$	m (kg): Mass v (m/s): Velocity	J
	$P.E.(\text{Potential Energy}) = mgh$	m (kg): Mass g: 10N/kg h (m): Height	J
	$X P(\text{Power}) = \frac{W \text{ or Energy change}}{\text{Time}}$	Energy change /Work done(J) Time (s)	J/s, W (watt)
3.1 Principles of Thermometry	$\theta = \frac{X_s - X_0}{X_{100} - X_0}$ ( <b>For Celsius scale only</b> )	Theta: Unknown temperature X <sub>0</sub> : "ice point", X <sub>100</sub> : Steam pt	°C
3.2 Thermal Properties of Matter	$Q(\text{heat energy}) = C_s \theta$	C: Heat capacity	J
	$Q = mc_s \theta$	m: mass c: Specific Heat Capacity	J
	$Q = ml_f$	$l_f$ : Latent heat of fusion	J
	$Q = ml_v$	$l_v$ : Latent heat of vapourisation	J
4.1: General Wave Properties	$f = \frac{1}{T}$	f: Frequency t (sec): Time	Hz
	$v = f \lambda$	v (m/s): Velocity λ (m): Wavelength f(1/t): Frequency	m/s
4.2: Light	Snell's Law: $\frac{\sin i}{\sin r} = n$	n = refractive index (ratio) i/r (°): angle of incidence/refraction <b>*Set calculator in degree mode.</b>	NA. Ratio.
	Condition: The angle of incidence must be in the less dense medium; angle r must be in the denser medium.		

4.2: Light	$\frac{c}{v} = \frac{\text{Real depth}}{\text{Apparent depth}} = \frac{\text{Ht of image}}{\text{Ht of object}} = n$	c (m/s): Speed of light in vacuum ( $3 \times 10^8$ m/s) v (m/s): Speed of light in medium.	NA. Ratio.
	$c = \sin^{-1} n$	c ( $^\circ$ ): Critical angle.	$^\circ$
5.1: Current Electricity	$I = \frac{Q}{t}$	I: Current (A) Q: Charge (Coulomb) t: Time (sec)	Coulomb, C
	$v = \frac{W}{Q}$	v : E.m.f. (Volts – V) W: Work done/energy of circuit (J) Q: Charge (Coulomb)	V, J/C
	$V = \frac{W}{Q}$	V: Potential Diff. (V) W: Work done/energy across circuit component Q: Amount of charge	V, J/C
	Ohm's Law: $V = IR$ Condition: Only for ohmic conductors.	R: Resistance ( $\Omega$ )	V
	$R = \dots \frac{l}{A}$	... : Resistivity ( $\Omega \text{ m}$ ) L: Length A: Cross-sectional Area	$\Omega$
5.2: Practical Electricity	$E = VIt = I^2 RT = \frac{V^2 t}{R}$		J
	$P = VI = I^2 R = \frac{V^2}{R}$	P = Power R = Resistance	W
5.3: Electromagnetic Induction	$\frac{V_s}{V_p} = \frac{N_s}{N_p} = \frac{I_p}{I_s}$		

